

Network Recorder NR-V2



Power Requirements	100-240 VAC 50/60Hz 7A
Power Supply	Antec Earth Watts EA 430 430W ATX 12V Power Supply
Operating System	MS Windows XP Pro SP2 OEM
Recovery Software	Acronis True Image OEM
USB Port	Back: Eight (8) ports Front: Two (2) ports
Drive Bays	External: 3" x 3.5" and 2" x 3.5" Internal: 1" x 3"
Hard Disk Drive – Data	Seagate ST3500320AS. 500GB, SATA2, 7200rpm, in Raid 1 (mirror) Configuration on Raid controller card. Two (2)
Hard Disk Drive – OS Base	Seagate ST3250410AS, 250GB, SATA, 7200rpm, 16MB NCQ. One (1)
Removable Drive Kit	Seagate ST3250410AS, 250GB, SATA2, 7200rpm, 16MB NCQ HDD installed onto ICY Dock. One (1)
Controller	Adaptec 1220SA, SATA 2 RAID, 2-Port, PCI-Express for Hard Disk Drive—Data Array
Port	One (1): Integrated RS232, One (1): IEEE1394a, One (1) Parallel, One (1) PCR Express x16 slot, One (1) PCI Experess xl slot, Two (2) PCI 2.2 slots.
Motherboard	Intel DQ35JO Core 2/Quad, Intel Q35 Chipset, FSB 1333/1066/800, Intel vPro Ready, Audio , Viedeo and Gigabit Ethernet Micro-ATX
SDRAM	4 GB 667MHzDDR2
CD Burner	Samsung DVDRW with CDBurner XO and Nero OEM installed.
Integrated Graphics Media Accelerator	Intel X3100
Integrated Gigabit Ethernet Controller	Intel 82566DM
Sound Card	Creative Labs SB Audiology 7.1 SB0610VP
Keyboard and Mouse	US English keytronics Lifetime Classic II and Logitech LX3 Optical
Operating Temperature	
Dimensions	7" H x 19" W x 17.7" D (with rounded handles) 4RU Rack Mount
Weight	

This specification information is preliminary and is subject to change without notification.