



PH-10

Dual-Sided with 24dB NRR, Flexible Dynamic Boom Mic

The PH-10 is the ultimate in passive noise reduction. This heavy-duty headset offers snug fitting, dual-sided monaural headphones with a dynamic, noise-canceling microphone for use in high noise environments. The PH-10 offers an Environmental Protection Agency (EPA) rated noise reduction rating (NRR) of 24 dB. Perfect for industrial and concert applications. Available with 4- or 5-pin male XLR connectors, as well as a 4-pin female XLR connector.

Wiring Diagram

Connection in headset		Wire color at cord termination
R SPK +	—	YEL
L SPK +	—	BLK
SPK -	—	RED
MIC +	—	WHT
MIC -	—	BLU
MIC SHIELD	—	SHIELD

PH-10 Specifications

Connector Termination

PH-10: XLR 4-pin Female

PH-10R: XLR 4-pin Male

PH-10R5: XLR 5-pin Male

Type

PH-10: Dual Sided Monaural

PH-10R: Dual Sided Monaural

PH-10R5: Dual Sided Stereo

Mic Type

Dynamic Noise-Canceling

Mic Sensitivity

-65dBV/Pa @1cm

Mic Frequency Range

200Hz - 6kHz

Mic Impedance

150Ω

Speaker Sensitivity

95dB SPL @1kHz, 1mW

Speaker Frequency Range

100Hz - 3kHz

Speaker Impedance

PH-10: 150Ω

PH-10R: 150Ω

PH-10R5: 300Ω per side

Weight

17oz. (not including cord)

Cord Length

5.5 ft.

Contact Information

Telex Communications, Inc.
12000 Portland Avenue South
Burnsville, Minnesota 55337
Telephone: 877-863-4169
Fax: (800) 323-0498

Form Number: 38109-702 Rev E

Date: December, 2007

Ordering Information

PH-10

Dual-Sided with 24dB NRR, Flexible Dynamic Boom Mic, & A4F Connector

Catalog Number: 70470-100

PH-10R

Dual-Sided Headset with 24dB NRR, Flexible Dynamic Boom Mic, & A4M Connector

Catalog Number: 70470-102

PH-10R5

Dual-Sided Headset with 24dB NRR, Flexible Dynamic Boom Mic, & A5M Connector

Catalog Number: 70470-201

This specifications information is preliminary and is subject to change without notification.

Brand names mentioned are the property of their respective companies.