

TELEX BTR-700/800/825 -vs- BTR-80N

Feature	Telex 700	Telex 800/825		Telex 80N	
	BASE STATION AND SYSTEM FEATURES				
RF FREQUENCY RANGE	518-608, 614-740 MHz	470-608, 614-746 MHz		482-608, 614-722 MHz	
FREQUENCY BANDS	5 (A2, B4, C3, C6 , G9)	18 F1, F2, F3, F4 H1, H2, H3, H4 A2, A3, A4 B3, B4, B6 C3, C4, C6 E88		32 F1, F2, F3, F4, F5, F6 H1, H2, H3, H4, F5, F6 A1, A2, A3, A4, A5, A6 B2, B3, B4, B5, B6 C3, C4, C5, C6 D4, D5, D6 E5, E6	"6" & "G9" BANDS ARE INTENDED FOR SALE AND USE OUTSIDE OF THE USA
TRANSMITTER OCCUPIED BANDWIDTH	100 KHz	100 KHz		25 KHz	
Simultaneous 2 Wire & 4 Wire Operation	NO	YES - Either Channel		YES - Each Channel	
BASE STATION ANTENNA (Supplied)	1/2 Wave	1/2 Wave		1/2 Wave	
FREQUENCY SCANNING	YES ClearScan®	YES ClearScan®		YES ClearScan®	
BASE STATION TRANSMIT POWER	50 & 5mW	100 & 10mW		249, 100, 50 & 10mW	
BASE STATION DUAL TRANSMIT ANTENNA OUTPUT	N/A	OPTIONAL		OPTIONAL	
WARRANTY	3 YRS	3 YRS		3 YRS	
USER ADJUSTABLE SQUELCH CONTROL	NO	NO		YES	
RF METER (Rx SIGNAL STRENGTH)	NO	NO		YES	
BELTPACK BATTERY GAUGE ON BTR DISPLAY	NO	NO		YES	
ABILITY TO TURN OFF TR Tx FROM BTR	NO	NO		YES	
AC or DC POWER OPERATION	YES - KIT	YES - KIT		YES	
AUXILIARY AUDIO ASSIGNABLE	NO	NO		YES	
WIRELESS TALK AROUND - WTA	YES	YES		YES	
STAGE ANNOUNCE - SA	YES	YES		YES	
INTELLIGENT POWER CONTROL (TR Tx POWER)	YES	YES		YES	
FIRST ON - LATCH OUT OPERATION WITH TONE WARNING	NO	NO		YES Tone Defeatable	
SELECTABLE DC POWER FEED ON Rx LINE	NO	NO		YES 9 volts DC	
	BELTPACK FEATURES				
	TR-700	TR-800	TR-825	TR-80N	TR-82N
BELTPACK CONSTRUCTION	METAL DIE CAST MAGNESIUM	METAL DIE CAST MAGNESIUM	METAL DIE CAST MAGNESIUM	METAL DIE CAST MAGNESIUM	METAL DIE CAST MAGNESIUM
BELTPACK BATTERY LIFE (6 AA Alkaline)	14 Hrs	14Hrs	11Hrs	10 Hrs	9 Hrs
BELTPACK BATTERY LIFE (BP-800NM)	11 Hrs	11 Hrs	9.5 Hrs	10 Hrs	8 Hrs
PROGRAMMABLE BUTTONS ON BELTPACK	YES	YES	YES	YES	YES
PROGRAMMING AT BELTPACK	YES	YES	YES	YES	YES
BELTPACK TRANSMIT POWER	AUTO; 5 - 50mW	AUTO; 5 - 50mW	AUTO; 5 - 50mW	AUTO; 5 - 50mW	AUTO; 5 - 50mW
SELECTABLE-	NO	NO	NO	YES - AUTO, 100, 50, 5mW	YES - AUTO, 100, 50, 5mW
BELTPACK LOW BATTERY INDICATOR	YES	YES	YES	YES	YES
BELTPACK LOW BATTERY TONE WARNING	NO	NO	NO	YES	YES Tone Defeatable
ABILITY TO DISPLAY FREQUENCY AT BELTPACK	YES	YES	YES	YES	YES
EXTRA PDA DEVICE REQUIRED FOR PROGRAMMING	NO	NO	NO	NO	NO
BELTPACK TETHERED PROGRAMMING TO BASE STATION	NO	NO	NO	NO	NO
USER ADJUSTABLE SQUELCH CONTROL	NO	NO	NO	YES	YES
RF METER (Rx SIGNAL STRENGTH)	NO	NO	NO	YES	YES