

### CSI-100

#### Bidirectional Coaxial Interface Board Option Kit for KP-32



The CSI-100 permits the use of existing, but unused 75  $\Omega$  video coaxial cable as an alternative to running new cable for a keypanel connection. The CSI-100 is a bidirectional; single-channel coaxial interface, which passes digital audio and control between KP-32 series keypanels, and CSI-200 coaxial interfaces connected to RTS intercom matrices. Installation of the CSI-100 is quick and simplified with no user settings. Existing KP-32 series keypanels can be retrofitted with the CSI-100 in about 15 minutes. In addition, KP-32 keypanels can be ordered with the CSI-100 option already installed.

## Specifications

---

**SNR @ +8dBu (A-weighted)**

>70dB

**THD+N @ +8dBu (un-weighted)**

<0.1%

**Frequency Response**

100Hz–20kHz  $\pm 1$ dB

**Operating Level**

+8dBu

**Maximum Level**

+20dBu

**Crosstalk**

< -70dB

**Coaxial Port**

BNC Female, 75  $\Omega$  impedance

**Power**

Supplied by keypanel

**Operating Temperature**

-20°C to 50°C (-4°F to 122°F)

**Storage Temperature**

-40°C to 85°C (-40°F to 185°F)

**Operating & Storage Humidity**

0 to 95% non-condensing

## Order Information

---

CSI-100 • CSI-100 • Bidirectional coaxial interface option kit

The specification information is preliminary and is subject to change without notification.  
Brand names mentioned are the property of their respective companies.